RAM No-Drill ™ Seat Bases

RAM Mounting Systems

SPECIFICATIONS

Placement Passenger side on the floor, in front of seat

Drilling Required No - uses existing seat bolts

Seat Configuration Bucket/Bench

Construction/Finish Steel/Black Powdercoat

Dimensions A = 17.57", B = 5.5", C = 11" Hole Center = 6.38" Pole or Pedestal Ordered Separately

Weight 10.7 lbs.



Shown In Use

Features

Installs in minutes with no drilling required

Misc.

Rugged steel construction

Lifetime warranty

RAM Mounting Systems 8410 Dallas Ave S Seattle, WA 98108 Phone: (206) 763-8361 Fax: (206) 763-9615 www.rammount.com support@rammount.com



RAM-VB-118



RMR-INS-VB-118

This document, including images, may not be reproduced partly or fully without the expressed written consent of National Products, Inc.

INSTALLATION INSTRUCTIONS

- 1. Remove the seat bolts that hold the passenger seat to the floor.
- 2. Loosely assemble legs to the base. Do not firmly tighten.
- 3. Place mounting base in front of the passenger seat. Align mounting legs to the seat bolt holes and tighten in place.
- 4. Gently lift the inside of the seat upward to allow the seat frame to clear the studs.
- 5. Place the base between the seat frame and align the holes in the base with the seat bolts.
- 6. Lower the seat back down over the no drill base and seat bolts.
- 7. Fully tighten factory hardware to secure base in place along with seat frame.

RAM Mounting Systems 8410 Dallas Ave S Seattle, WA 98108 Phone: (206) 763-8361 Fax: (206) 763-9615 www.rammount.com support@rammount.com



RMR-INS-VB-118

This document, including images, may not be reproduced partly or fully without the expressed written consent of National Products, Inc.